

2026 Crown Stocks Rules



The rules and/or regulations set forth herein provide for the orderly conduct of racing events and to establish minimum acceptable requirements of such events. These rules shall govern the condition of all such events. All participants are deemed to have complied with these rules. No expressed or implied warranty of safety shall result from publications of or compliance with these rules and/or regulations. Rules are intended as a guide for the conduct of the sport and are in no way a guarantee against injury or death to a participant. • Speedway Officials shall be empowered to permit minor deviations from any of the specifications herein or impose any further restrictions that in his/her opinion does not alter the minimum acceptable requirements. No expressed or implied warranty of safety shall result from such alteration of specifications. • Speedway reserves the right to update, modify, and/or delete rules at any time deemed necessary to ensure safety, fair competition or any other reason that may be appropriate. All discussions with officials must be conducted in a professional manor. • Cars, parts and or equipment will not be considered as having been approved by having passed through inspection at any time or number of times unobserved or undetected. • Any interpretation or deviation of these rules is left to the officials. Any decision of and by Speedway Officials is final. • Unsportsmanlike-like conduct can carry a minimum \$100.00 fine and/or suspension. All fines will be added to the point's fund at the end of the racing season. • No phones or communication devices in the car. • Track reserves the right to swap computers amongst competitors at any time.

A. SPIRIT OF THE RULES – The creation of an affordable, entry-level way to enter stock car oval racing. Keeping the cars very stock is the priority. Changes not listed in these rules are not allowed.

B. Cars – Only the Ford Crown Vic, Mercury Grand Marquis, Ford Crown Victoria Police Interceptor, or Lincoln Town Car 1995 and newer.

C. Drivers – Must wear a clearly-labeled helmet that meets or exceeds the 2015 SA Snell or SFI 31.2 standards. Fire suit is mandatory. Racing shoes and racing gloves are required. The use of an approved neck brace or Han's style device is required.

D. Car Number – Numbers must appear on both front doors and on the roof. Door and roof numbers shall be a minimum of 18" tall and 3" in line thickness. Numbers must contrast in color (light vs dark) from car color. The roof number needs to be facing the passenger side of the car. There must be a 6" white car number in the upper corner of the windshield on the passenger side of the car.

E. Raceceiver – All competitors will be required to use a working Raceceiver to compete.

F. Tech – Car must go thru inspection at its first visit to the track. After each feature the top 3 finishers and any other cars selected will go to tech. Those drivers and 2 crew members can assist with tech on those cars.

G. Cheating – 1st offense will bring driver and car disqualification from that event. A 2nd offense will bring a driver and/or car a possible ban from competition.

H. DRIVE TRAIN

1. Engine – Must remain an entirely stock 4.6L SOHC engine (No high compression dome top piston versions). Manifold stock. Air filter stock. AC compressor, lines, and ac/heater core box in engine compartment may be removed. Must contain water only. Manual fan allowed.
2. Battery – **Must be securely mounted and covered.** May remain in stock location or battery may be moved inside drivers compartment.
3. Master Switch – Master ON-OFF switch must be located in the center of the car, clearly marked and within easy access of the driver as well as access from outside both window openings.
4. Exhaust – Exhaust is 2-1/2" max. No X, H, or Y pipes. Pipes must go beyond the driver area and exit to the side or rear. Catalytic converter may be replaced with pipe
5. Transmission – Must remain entirely stock.
6. Rear End – Must remain entirely stock. Factory gear only 2.73-3.73 ratios only. No aftermarket lockers. You may weld the spider gears or use factory posi-traction. 2002 and older cars may use 4.10 and numerically lower ratios.

I. INTERIOR

1. Roll Cage – Minimum 4-point cage, rear down bars are optional, made with 1 3/4 x .095 tubing with 4 curved door bars on the driver's side and 4 straight bars can be used on the passenger side. Must have a bar that connects left and right legs of hoop behind driver's seat just above the driveshaft tunnel and another one welded at approximately half the distance from the top of driveshaft tunnel to the roof. Cage must be welded to the frame and not the floor pan. A driver's door plate is recommended. No offset cages. All roll cages must be painted.
2. Seat & Belts – A racing seat is required along with a 5-point racing harness. Belts can be no older than 5 years past the clearly marked manufacture dates on them.
3. Window Net – A properly mounted window net is mandatory and must be used anytime on track.
4. Steering Column – Must remain stock. Adding of a quick disconnect steering wheel is allowed.
5. Windshield – Must remain stock or Lexan or metal screen (2 half inch bars in front of driver for protection if running screen) and strapped in place. All other glass must be removed. All mirrors must be removed.
6. Dash –All flammable material can be removed.
7. Pedals – Must remain stock.
8. Ballast – No adding of any weight to the entire car. Track can add weight to any competitor at any time.

J. EXTERIOR

1. Suspension – No altering of the suspension including sway bar links. No spacers of any kind. No air rides. No cutting, no heating, or no lowering of springs. Shocks and springs can only be replaced by same stock parts or OEM replacements. Front and rear springs must match coil for coil, free height, and wire diameter. (Can cut two 2" holes above rear shocks to access top shock nut).
2. Caster & Camber – You may adjust as factory adjustments allow. May run aftermarket camber bolts (only Moog Part#K100094 or other aftermarket equivalent manufacture)
3. Tires – All season tires only. These tire sizes only 235/55/17, 225/60/16, and 215/70/15. No high performance tires. No directional tires. Nothing under **350** tread wear or any tire that cost \$175.00 or more. No autocross tires. No tire soaking or treating.
4. Wheels – Must be steel stock wheels. All 4 wheels must be the same size and offset. No wheel spacers. No offset wheels on cars 2003 and newer. 2002 and older cars may use dodge charger factory 17-inch steel wheels.
5. Bumpers –May use a stock bumper or 1.75" pipe front bumper. 8" stub out from frame of car and bumper must be looped back into frame. One top loop is permitted with no bracing of any kind. no square tubing. if the bumper does not conform to these rules, you will be forced to cut the bumper off and race without one for the night.
6. Hood/Trunk – Must have hood type pins for easy access by track officials. No bolting down.

K. Car Claim

1. Any competitor finishing the race on the lead lap can claim a competitor's car finishing in the top 5 ahead of them.
2. The price to claim the car is \$4500.00. This will be less seat and seat belts.
3. Failure to honor claim will result in loss of money and points earned in that and event and a minimum of a 1 race suspension.
4. Track reserves the right to deny claim if considered to be in spite or from more than one party.
5. Track reserves the right to claim any car winning 3 features in one season.

L. Major Infractions

1. If you have been caught with any performance enhancing computers, or performance aftermarket parts, the car and the driver may be banned from competition, either temporarily or permanently.

M. Minimum Weight

1. A minimum weight rule will be implemented in the near future.